



A-LINK®

A-LINK SD24GS 24 Port 10/100/1000MB Ethernet Switch Web Smart

A-LINK SD24GS is 24-port Gigabit Switch with autosensing ports and Web management interface. Support; Port based VLAN, Tag based VLAN, Port rate control, QoS etc.

Product specification :

• Standards :

IEEE 802.3 10BASE-T
IEEE 802.3u 100BASE-TX
IEEE 802.3x Flow Control
IEEE 802.3ab 1000BASE-T
IEEE 802.1x

• Autosence :

Auto MDI / MDI-X detects and corrects cabling errors.

• MAC address table :

8000
Automatic address learning and address aging

• Buffer memory :

480Kb

• Transmission mode :

Store-and-forward
Support up to 9Kb jumbo frame

• Switch fabric :

46Gbps forwarding capacity

• Interface :

24 x 10/100/1000 Mbps RJ-45 ports

• Panel indicators :

Per unit: power
Per port: link / activity

• Management :

Web management interface
RS-232 port command line interface
Support:
- Port based VLAN
- Tag based VLAN
- Trunk
- Port mirroring
- QoS
- Port based rate limit control
- IP setting through Web management
- Storm control
(ICMP, Broadcast, Multicast, Flooded unicast)
- SNMP, LACP, RTSP, IGMP snooping
- Backup and restore current configuration
- Firmware upgrade

• Power :

AC 100-240V 50/60Hz internal power
max. 29W

• Dimensions and weight :

440 x 141 x 44mm (L x W x H)
1600g net weight

• Temperatures and humidity :

0-40°C operating, 0-70°C storage
5 - 95% non-condensing

• Compliance :

CE, FCC, RoHS

• A-LINK Retail package contains :

- Switch
- Power cable

• Package info :

Export cartoon size 5pcs

• Ean / Order code :

6418949026120

A-LINK is a registered trademark of A-LINK.
<http://www.a-link.com>
All rights reserved

SD24GS specs UK 29.01.09

